

产品型号/Model: TB-64	工作电压 Operating Voltage	A:27V; B:27V; C:8V	
	工作电流 Operating Current	A:5A; B:0.5A; C:1.4A	
	工作时间 Operating Time	≥50s	
	激活时间 Activation Time	≤1s	
	噪音电压 Noise Voltage	—	
	表面温度 Surface Temperature	—	
	工作温度 Operating temperature	-40℃~+50℃	
	激活方式 Activation Mechanism	机械激活 Mechanical	
	外形尺寸 Envelope Dimension	Φ30mm×95mm	
	重量 Weight	≤200g	
	其他要求 Additional requirements	过载/Overload Resisitance: — 旋转/Rotation: —	

产品型号/Model: TB-65	工作电压 Operating Voltage	A:14V~27V; B:19V~37V	
	工作电流 Operating Current	A:8.0A; B:0.8A	
	工作时间 Operating Time	≥4s	
	激活时间 Activation Time	≤100ms	
	噪音电压 Noise Voltage	—	
	表面温度 Surface Temperature	—	
	工作温度 Operating temperature	-40℃~+50℃	
	激活方式 Activation Mechanism	机械激活 Mechanical	
	外形尺寸 Envelope Dimension	Φ38mm×45mm	
	重量 Weight	≤0.18kg	
	其他要求 Additional requirements	过载/Overload Resisitance: — 旋转/Rotation: —	