

	产品型号/Model: TB-86 工作电压 Operating Voltage	A: 8V~16V B: 8V~16V
	工作电流 Operating Current	A: 3±0.5A; B: 1.0A
	工作时间 Operating Time	A: ≥50s; B: ≥50s
	激活时间 Activation Time	≤0.5s
	噪音电压 Noise Voltage	—
	表面温度 Surface Temperature	—
	工作温度 Operating temperature	-40℃~+50℃
	激活方式 Activation Mechanism	过载激活: 2000g, 3ms/2500g, 3ms Over load: 2000g, 3ms/2500g, 3ms
	外形尺寸 Envelope Dimension	Φ38mm×40mm
	重量 Weight	150±20g
	其他要求 Additional requirements	过载/Overload Resisitance: — 旋转/Rotation: —

	产品型号/Model: TB-87 工作电压 Operating Voltage	≥16V
	工作电流 Operating Current	>20mA
	工作时间 Operating Time	≥30s
	激活时间 Activation Time	≤0.15s
	噪音电压 Noise Voltage	—
	表面温度 Surface Temperature	—
	工作温度 Operating temperature	-40℃~+50℃
	激活方式 Activation Mechanism	机械激活, 激活能量: 100g·cm Activation energy : 100g·cm
	外形尺寸 Envelope Dimension	Φ14mm×27.5mm
	重量 Weight	—
	其他要求 Additional requirements	过载/Overload Resisitance: — 旋转/Rotation: —