



Telecommunications Lithium battery Pack 48V/100Ah



基本参数 Basic Specifications

电池型号	Battery model	48V100Ah
标称电压	Nominal voltage	51.2V
标称容量	Nominal capacity	100AH
充电电压	Charge voltage	58.4V
放电截止电压	Discharge cut-off voltage	40V
建议充电电流	Suggested charge current	≤50A
建议放电电流	Suggested discharge current	≤100A
瞬间最大电流	Maximum current	125A(30S)
常温循环寿命	Life cycle at normal temperature	3000次 times
通讯方式	Communication mod	2个RS485和1个RS232CAN 干接点 (可选)
充电温度	Charge temperature	0~45°C
放电温度	Discharge temperature	-20~60°C
接口型号	Model of the interface	充电口:2P栅格端子 放电口:2P栅格端子
电池重量	Battery weight	大约42KG
电池尺寸	Battery size	W446xT177x(L400-450mm可调整 adjustable)

基站后背式铁锂电池系统

Base station back type iron lithium battery system

应用领域:适用于小容量接入网设备、远端交换局、移动通信设备、传输设备、卫星地面站和微波通讯设备等备电

优点:具备集中控制、电池维护和管理的功能,满足无人值守的要求;可以通过手机APP来进行实时监控。

Applications: It was suitable for power supply such as small capacity access network devices, remote exchange bureau, mobile communication devices, transmission devices, satellite earth station and microwave communication devices

Advantages: It had the function of central control, battery maintenance and management to meet the requirements of no one on duty; it could be monitored in real time through the mobile APP

Timely Contacts: 7/24 whatsapp: 008613823653608
Payment term: D/P, D/A, O/A flexible and negotiable